

Model 4216 Vibration Analyzer with LED Strobe

Features:

Model 4216 Vibration Analyzer with LED Strobe Light is a portable tunable filter vibration analyzer that uses standard 100 mV/g accelerometers. It provides direct vibration measurements in velocity, displacement and acceleration. The complete package is powered by either the internal rechargeable battery or by 115 / 230 VAC shop power. Operators can use the 4216 to troubleshoot vibration problems or provide on-site dynamic balancing using the LED Strobe light for fans, motors, grinding wheels, spindles, crushers, and other rotating machinery.

Model 4216 Includes:

Model 4216 Vibration Analyzer
Model 601 Pickup and 15' Pickup Cable
Model 052 Magnetic Base Clamp
Model 298 LED Strobe Light
Model 060-15 LED Strobe Cable
Model 037P Carrying Case
Manual and Calibration Certificate

Specifications:

AMPLITUDE RANGE: 0.03, 0.1, 0.3, 1, 3, 10, 30, 100 English mils (peak-to-peak), inches per second (peak) and G's (peak) full-scale

MINIMUM SENSITIVITY: Displacement 0.000001 inch
Velocity 0.001 inch per second (ips)
Acceleration 0.001 G's

ACCURACY: 5% of Full Scale

FREQUENCY RANGE: 200 to 200,000 RPM (Total over 3 ranges)

TUNABLE FILTER: Range X1: 200 to 2,000
Range X10: 2,000 to 20,000
Range X100: 20,000 to 200,000



OUTPUTS: Scope Signal: 1V p-p for FS amount meter
Counter Signal: Pulse +12V
Strobe: Model 298 LED Strobe Light

INPUTS: 2 for ICP 100 mV/g Accelerometer Pickups
Balmac Model 601 Accelerometer

POWER: Line Voltage 115/230 VAC, 50/60 Hz
Internal Battery 12 VDC


BATTERY Rechargeable Sealed Lead Acid
Operating Time: 10 hours
Recharge Time: <24 hours

OPERATING TEMPERATURE 32° to 122°F (0° to 50°C)

STORAGE TEMPERATURE -40° to 122°F (-40° to 50°C)

DIMENSIONS 11 3/4" x 6 3/4" x 9 1/4" (30 x 17 x 24 cm)

WEIGHT Unit Only: 10 lbs (4.5 kg)
Complete Package: 20 lbs (9 kg)



BALMAC INC.
8205 Estates Pkwy, Ste N
Plain City, OH 43064-8080 USA

Telephone: 614-873-8222
Email: sales@balmacinc.com

balmacinc.com